


壁装式相位转换装置插头
货号 3346




带螺钉接线端子

技术信息

| | |
|------|----------|
| 伏特 | 32 A |
| 极数 | 4 p |
| 电压 | 400 V |
| 钟点位置 | 6 h |
| 赫兹 | 50-60 Hz |
| 连接方式 | 螺钉连接 |
| 触点 | 标准 |
| 防护等级 | IP 44 |
| 重量 | 399 克 |
| 认证标志 | EAC, CQC |

图纸



| Drawing 2 MB 32 | Amp. Poles | 16 | | | 32 | | |
|---|---------------|----------------------------|------|------|----------------------------|-------|-------|
| | | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 87 | 100 | 100 | 128 | 128 | 128 |
| | b | 64 | 75 | 75 | 84 | 84 | 84 |
| | c | 93 | 106 | 110 | 133 | 133 | 135 |
| | d | 40 | — | — | — | — | — |
| | d1 | — | 10.5 | 10.5 | 11 | 11 | 11 |
| | e | 50.5 | 59 | 59 | 68 | 68 | 68 |
| | f | 4.5 | 5 | 5 | 5.3 | 5.3 | 5.3 |
| | g | 4 | 4 | 4 | 4 | 4 | 4 |
| | h | 122 | 133 | 135 | 169 | 169 | 170 |
| | M | 20 | 20 | 20 | 32 | 32 | 32 |
| | M* | 1x20 (blind) to be cut out | | | 2x25 (blind) to be cut out | | |
| Max. cable diam. (mm) | | 15 | 15 | 15 | 18/25 | 18/25 | 18/25 |
| Terminal for cond. cross section (mm ²) min.-max. | | 1 | 1 | 1 | 2.5 | 2.5 | 2.5 |
| | | -2.5 | -2.5 | -2.5 | -6 | -6 | -6 |